Package: groupedHyperframe (via r-universe)

November 10, 2026

Type Package

Title Grouped Hyper Data Frame

Version 0.4.6

Date 2026-10-11

Description Extensions of ``hyper data frame'' (from package 'spatstat.geom') with a grouping structure. The author has retired from academic research. Accordingly, this package should not be considered a validated tool for use in peer-reviewed publications or as the basis for grant applications. Backward compatibility with user-code published in <doi:10.1093/bioinformatics/btaf430> is not maintained in versions >= 0.4.0 (June 2026) of this package. The authors of those publications are the appropriate contacts for reproducibility inquiries.

Encoding UTF-8

License GPL-2

Language en-US

Depends R (>= 4.6)

Imports cli, spatstat.geom

Suggests survival, spatstat.data

Config/roxygen2/version 8.1.1

Config/roxygen2/markdown TRUE

NeedsCompilation no

Author Tingting Zhan [aut, cre]

Maintainer Tingting Zhan <tingtingzhan@gmail.com>

Repository https://tingtingzhan.r-universe.dev

Date/Publication 2026-10-11 15:30:02 UTC

RemoteUrl https://github.com/cran/groupedHyperframe

RemoteRef HEAD

RemoteSha e79512f6596a7d5cf4abb8f7b1322abb7521a1f0

Contents

groupedHyperframe-package 2
aggregate.hyperframe 3
aggregate2 3
aug4gam 4
is.vectorlist 5
pppBy 6

Index **7**

`groupedHyperframe-package`
groupedHyperframe: Grouped Hyper Data Frame

Description

Extensions of "hyper data frame" (from package 'spatstat.geom') with a grouping structure. The author has retired from academic research. Accordingly, this package should not be considered a validated tool for use in peer-reviewed publications or as the basis for grant applications. Backward compatibility with user-code published in doi:10.1093/bioinformatics/btaf430 is not maintained in versions >= 0.4.0 (June 2026) of this package. The authors of those publications are the appropriate contacts for reproducibility inquiries.

Note

This R package author has retired from academic research.

Accordingly, this package should not be considered a validated tool for use in peer-reviewed publications or as the basis for grant applications.

Backward compatibility with user-code published in the following publications is not maintained in versions >= `0.4.0` of this package. The authors of those publications are the appropriate contacts for reproducibility inquiries.

doi:10.1093/bioinformatics/btaf430

Author(s)

Maintainer: Tingting Zhan <tingtingzhan@gmail.com>

Authors:

- Tingting Zhan <tingtingzhan@gmail.com>

aggregate.hyperframe *Aggregate Hyper Data Frame*

Description

To aggregate a hyperframe.

Usage

```
## S3 method for class 'hyperframe'
aggregate(x, by, ...)
```

Arguments

x	hyperframe
by	two-sided formula, whose right-hand-side contains only the regular-column names of the input x
...	additional parameters of the function aggregate.data.frame, *except for* simplify

Value

The S3 method aggregate.hyperframe() returns a hyperframe.

Examples

```
spatstat.data::demohyper |>
 aggregate(by = . ~ Group, FUN = unique)

spatstat.data::flu |>
 aggregate(by = . - frameid ~ virustype:stain, FUN = unique)

spatstat.data::osteo |>
 aggregate(by = . - brick ~ shortid, FUN = unique)
```

aggregate2 *Aggregate, an Alternative formula-Interface*

Description

An alternative aggregation function with a formula-interface, to avoid the cbind-operation in the function aggregate.formula.

Usage

```
aggregate2(data, by, ...)
```

Arguments

`data`	a data.frame
`by`	a two-sided formula
`...`	additional parameters of the function aggregate.data.frame, except for `simplify`

Details

The cbind-operation in the function aggregate.formula messes up with column(s) that are

factor and treat them as integer

Surv and treat them as matrix

The function aggregate.data.frame only accepts a list of factors for the parameter `by`.

Therefore, the function `aggregate2()` is created to take care of the factor and Surv columns of the input, with a formula-interface.

Value

The function `aggregate2()` returns a data.frame.

Note

The function aggregate.data.frame is the workhorse of the function aggregate.formula.

The function as.hyperframe.data.frame is **designed** to handle the list-columns returned by the function aggregate.

---

aug4gam *Augment Hypercolumn(s) for gam*

Description

Augment *all* numeric vector hypercolumns in a hyperframe for gam.

Usage

```
aug4gam(x, ...)

## S3 method for class 'data.frame'
aug4gam(x, ...)

## S3 method for class 'hyperframe'
aug4gam(x, ...)

## S3 method for class 'vectorlist'
aug4gam(x, ...)
```

Arguments

x	see **Usage**
...	additional parameters, currently of no use

Value

The S3 generic function aug4gam() returns a data.frame.

Author(s)

Tingting Zhan, Erjia Cui

---

is.vectorlist *Vector-List*

Description

To determine if an R object is a list of vectors with the same storage.mode, length and attributes.

Usage

```
is.vectorlist(
  x,
  mode = c("logical", "integer", "numeric", "double", "character")
)
```

Arguments

x	a listof
mode	character scalar other than 'any', 'complex' and 'raw', see the function is.vector

Value

The function is.vectorlist() returns a logical scalar.

Examples

```
spatstat.data::Kovesi$values |>
 is.vectorlist(mode = 'character') |>
 stopifnot()
spatstat.data::Kovesi$values |>
 is.vectorlist(mode = 'numeric')
```

pppBy *Hyper Data Frame with One-and-Only-One ppp-Hyper Column*

Description

To create a hyper data frame with one-and-only-one ppp-hyper column.

Usage

```
pppBy(
  marks,
  coords = ~x + y,
  by,
  data,
  window = owin(xrange = range(.x), yrange = range(.y)),
  ...
)
```

Arguments

marks	one-sided formula, e.g., ~ m1+m2, where m_i's are one or more marks
coords	one-sided formula, variable names of the x- and y-coordinates in data. Default value is ~x+y.
by	two-sided formula
data	data.frame
window	observation window owin, default value is the x- and y-span of coords in data.
...	additional parameters of the function ppp

Value

The function pppBy() returns a hyper data frame with one-and-only-one ppp-hyper column.

Index

aggregate, *3, 4*
aggregate.data.frame, *3, 4*
aggregate.formula, *3, 4*
aggregate.hyperframe, 3
aggregate.hyperframe(), *3*
aggregate2, 3
aggregate2(), *4*
as.hyperframe.data.frame, *4*
attributes, *5*
aug4gam, 4
aug4gam(), *5*

cbind, *3, 4*
character, *5*

data.frame, *4–6*

factor, *4*
formula, *3, 4*, *6*

gam, *4*
groupedHyperframe
(groupedHyperframe-package), 2
groupedHyperframe-package, 2

hyperframe, *3, 4*

integer, *4*
is.vector, *5*
is.vectorlist, 5
is.vectorlist(), *5*

length, *5*
list, *4, 5*
listof, *5*
logical, *5*

marks, *6*
matrix, *4*

numeric, *4*

owin, *6*

ppp, *6*
pppBy, 6
pppBy(), *6*

storage.mode, *5*
Surv, *4*

vector, *4, 5*